



Vehicle Safety Inspection

\$99.00

VEHICLE COMPONENTS INSPECTED											
OK	NEEDS REPAIR	REPAIR DATE	ITEM	OK	NEEDS REPAIR	REPAIR DATE	ITEM	OK	NEEDS REPAIR	REPAIR DATE	ITEM
			1. BRAKE SYSTEM				6. SAFE LOADING				10. TIRES
			a. Service Brakes				a. Part(s) of vehicle or condition of loading such that the spare tire or any part of the load or dunnage can fall onto the roadway.				a. Tires on any steering axle of a power unit.
			b. Parking Brake System				b. Protection against shifting cargo.				b. All other tires.
			c. Brake Drums or Rotors				c. Container securement devices on intermodal equipment.				11. WHEELS AND RIMS
			d. Brake Hose								a. Lock or Side Ring
			e. Brake Tubing								b. Wheels and Rims
			f. Low Pressure Warning Device								c. Fasteners
			g. Tractor Protection Valve								d. Welds
			h. Air Compressor								12. WINDSHIELD GLAZING
			i. Electric Brakes								Requirements and exceptions as stated pertaining to any crack, discoloration or vision reducing matter (reference 393.60 for exceptions).
			j. Hydraulic Brakes				7. STEERING MECHANISM				13. WINDSHIELD WIPERS
			k. Vacuum Systems				a. Steering Wheel Free Play				Any power unit that has an inoperative wiper, or missing or damaged parts that render it ineffective.
			2. COUPLING DEVICES				b. Steering Column				14. OTHER
			a. Fifth Wheels				c. Front Axle Beam and All Steering Components Other Than Steering Column				List any other condition(s) which may prevent safe operation of this vehicle.
			b. Pintle Hooks				d. Steering Gear Box				
			c. Drawbar/Towbar Eye				e. Pitman Arm				
			d. Drawbar/Towbar Tongue				f. Power Steering				
			e. Safety Devices				g. Ball and Socket Joints				
			f. Saddle-Mounts				h. Tie Rods and Drag Links				
			3. EXHAUST SYSTEM				i. Nuts				
			a. Exhaust system leaking forward of or directly below the driver/sleeper compartment.				j. Steering System				
			b. Bus exhaust system leaking or discharging in violation of standard.				8. SUSPENSION				
			c. Exhaust system likely to burn, char, or damage the electrical wiring, fuel supply, or any combustible part of the motor vehicle.				a. Any U-bolt(s), spring hanger(s), or other axle positioning part(s) cracked, broken, loose or missing resulting in shifting of an axle from its normal position.				
			4. FUEL SYSTEM				b. Spring Assembly				
			a. Visible leak.				c. Torque, Radius or Tracking Components				
			b. Fuel tank filler cap missing.				9. FRAME				
			c. Fuel tank securely attached.				a. Frame Members				
			5. LIGHTING DEVICES				b. Tire and Wheel Clearance				
			All lighting devices and reflectors required by Part 393 shall be operable.				c. Adjustable Axle Assemblies (Sliding Subframes)				